



Architectural Cable Railing Catalog

Table of Contents

Tensioning Systems.....	3	Additional Hardware.....	16
Toggle Swage Stud Turnbuckle	3	Flat End.....	15
Jaw and Swage Stud Turnbuckle.....	3	Threaded Lag Insert	16
Swage Stud and Swage Stud Turnbuckle	3	Plain Lag Insert.....	16
Threaded Rod and Swage Stud Turnbuckle	4	Hanger Bolt.....	16
Lag and Swage Stud Turnbuckle	4	Dome Nut.....	17
Deck Toggle and Swage Stud Turnbuckle.....	4	Ball End.....	17
Fork and Swage Stud Turnbuckle.....	5	Hex Nut	17
Eye and Eye Turnbuckle.....	5	Threaded Rod	18
Hook and Hook Turnbuckle.....	5	Flat Washer.....	18
Jaw and Jaw Open Turnbuckle.....	6	Non Welded Lag Eye Bolt.....	18
Open Turnbuckle Body.....	6	Non Welded Eye Bolt	19
Pipe Turnbuckle Body	6	30° Angled Washer	19
Jaw and Jaw Pipe Turnbuckle.....	7	Standoff Washer for Round Post	19
Toggle and Toggle Pipe Turnbuckle.....	7	30° Countersunk Angle Washer	20
Drop Pin and Swage Stud Turnbuckle	7	30° Countersunk Angle Washer for Round Post.....	20
Stub End Turnbuckle.....	8	Sleeve.....	20
End Fittings	8	Plain Ball Swage.....	21
Swage Stud	8	Single Shank Ball Swage.....	21
Hand Swage XL Swage Stud	8	Double Shank Ball Swage	21
Hand Swage Stud	9	Stainless Steel Cable.....	22
Hand Swage Short Stud.....	9	1x19 Cable	22
Lifeline Threaded Stud.....	9	Tools.....	22
Swage Toggle	10	Hand Swage Tool.....	22
Swage Marine Eye.....	10		
Swage Jaw	10		
Fork Swage	11		
Deck Toggle Swage	11		
Stemball Swage	11		
Dome Swage.....	12		
Hand Swage Lag Stud.....	12		
Hand Swage Jaw	12		
Hand Swage Toggle.....	13		
Hand Swage Deck Toggle	13		
Hand Swage Drop Pin Stud.....	13		
Stud Receiver.....	14		
Invisi-Stud	14		
Adjustable Swage Stud	14		
Streamline Fixed Jaw.....	15		
Streamline Adjustable Jaw.....	15		

These systems and parts cannot be returned due to safety risks associated with used materials

Tensioning Systems

Toggle Swage Stud Turnbuckle s.s. T316



* Hand Swage

Item Number:	Cable Size:	Thread:	Pin Diameter:	Jaw Opening:	Length:
TSS316SSTB1/4-1/8	1/8"	1/4"	0.23"	0.40"	7"
TSS316SSTB1/4-3/16	3/16"	1/4"	0.23"	0.40"	7-1/8"
TSS316SSTB1/4-1/8-HS*	1/8"	1/4"	0.23"	0.40"	7"
TSS316SSTB1/4-3/16-HS*	3/16"	1/4"	0.23"	0.40"	7-1/8"
TSS316SSTB5/16-3/16	3/16"	5/16"	0.23"	0.40"	8"
TSS316SSTB5/16-1/4	1/4"	5/16"	0.23"	0.40"	8-1/4"
TSS316SSTB3/8-1/4	1/4"	3/8"	0.36"	0.52"	9-1/2"

Jaw and Swage Stud Turnbuckle s.s. T316



* Hand Swage

Item Number:	Cable Size:	Thread:	Pin Diameter:	Jaw Opening:	Length:
SSJSSTB1/4-1/8	1/8"	1/4"	1/4"	0.36"	6-5/8"
SSJSSTB1/4-3/16	3/16"	1/4"	1/4"	0.36"	6-3/4"
SSJSSTB1/4-1/8-HS*	1/8"	1/4"	1/4"	0.36"	6-5/8"
SSJSSTB1/4-3/16-HS*	3/16"	1/4"	1/4"	0.36"	6-3/4"
SSJSSTB5/16-3/16	3/16"	5/16"	5/16"	0.45"	7-1/2"
SSJSSTB5/16-1/4	1/4"	5/16"	5/16"	0.45"	7-3/4"
SSJSSTB3/8-1/4	1/4"	3/8"	11/32"	0.50"	9-1/4"

Swage Stud and Swage Stud Turnbuckle s.s. T316



* Hand Swage

Item Number:	Cable Size:	Thread:	Pipe Length:	Length:
SSSSTB316SS1/4-1/8	1/8"	1/4"	3-3/4"	7-3/4"
SSSSTB316SS1/4-3/16	3/16"	1/4"	3-3/4"	8-3/4"
SSSSTB316SS1/4-1/8-HS*	1/8"	1/4"	3-3/4"	7-3/4"
SSSSTB316SS1/4-3/16-HS*	3/16"	1/4"	3-3/4"	7-3/4"
SSSSTB316SS5/16-3/16	3/16"	5/16"	4-3/16"	9-3/16"
SSSSTB316SS5/16-1/4	1/4"	5/16"	4-3/16"	10-3/16"
SSSSTB316SS5/16-1/4-HS*	1/4"	5/16"	4-3/16"	10-3/16"
SSSSTB316SS3/8-1/4	1/4"	3/8"	5"	11-3/8"

Tensioning Systems

Threaded Rod and Swage Stud Turnbuckle s.s. T316



* Hand Swage

Item Number:	Cable Size:	Thread:	Pipe Length:
TRSS316SSTB1/4-1/8	1/8"	1/4"	3-3/4"
TRSS316SSTB1/4-3/16	3/16"	1/4"	3-3/4"
TRSS316SSTB1/4-1/8-HS*	1/8"	1/4"	3-3/4"
TRSS316SSTB1/4-3/16-HS*	3/16"	1/4"	3-3/4"
TRSS316SSTB5/16-3/16	3/16"	5/16"	4-3/16"
TRSS316SSTB5/16-1/4	1/4"	5/16"	4-3/16"
TRSS316SSTB5/16-1/4-HS*	1/4"	5/16"	4-3/16"
TRSS316SSTB3/8-1/4	1/4"	3/8"	5"

Lag and Swage Stud Turnbuckle s.s. T316



* Hand Swage

Item Number:	Cable Size:	Thread:	Length:
LSS316SSTB1/4-1/8	1/8"	1/4"-20	3-3/4"
LSS316SSTB1/4-3/16	3/16"	1/4"-20	3-3/4"
LSS316SSTB1/4-1/8-HS*	1/8"	1/4"-20	3-3/4"
LSS316SSTB1/4-3/16-HS*	3/16"	1/4"-20	3-3/4"
LSS316SSTB5/16-3/16	3/16"	5/16"-18	4-3/16"
LSS316SSTB5/16-1/4	1/4"	5/16"-18	4-3/16"
LSS316SSTB3/8-1/4	1/4"	3/8"-16	5"

Deck Toggle and Swage Stud Turnbuckle s.s. T316



* Hand Swage

Item Number:	Cable Size:	Thread:	Pipe Length:	Screw Size:
DTSSTBSS1/4-1/8	1/8"	1/4"-20	3-3/4"	1/4"
DTSSTBSS1/4-3/16	3/16"	1/4"-20	3-3/4"	1/4"
DTSSTBSS1/4-1/8-HS*	1/8"	1/4"-20	3-3/4"	1/4"
DTSSTBSS1/4-3/16-HS*	3/16"	1/4"-20	3-3/4"	1/4"
DTSSTBSS5/16-3/16	3/16"	5/16"-18	4-3/16"	5/16"
DTSSTBSS5/16-1-4	1/4"	5/16"-18	4-3/16"	5/16"
DTSSTBSS3/8-1/4	1/4"	3/8"-16	5"	3/8"

Tensioning Systems

Fork and Swage Stud Turnbuckle s.s. T316



* Hand Swage

Item Number:	Cable Size:	Thread:	Pin Diameter:	Jaw Opening:	Length:
MFSSSS1/4-1/8	1/8"	1/4"-20	1/4"	0.32"	6-7/8"
MFSSSS1/4-3/16	3/16"	1/4"-20	1/4"	0.32"	7-1/8"
MFSSSS1/4-1/8-HS*	1/8"	1/4"-20	1/4"	0.32"	6-7/8"
MFSSSS1/4-3/16-HS*	3/16"	1/4"-20	1/4"	0.32"	6-7/8"
MFSSSS5/16-3/16	3/16"	5/16"-18	5/16"	0.40"	8-3/8"
MFSSSS5/16-1/4	1/4"	5/16"-18	5/16"	0.40"	8-5/8"
MFSSSS3/8-1/4	1/4"	3/8"-16	3/8"	0.47"	10-3/16"

Eye and Eye Turnbuckle s.s. T316



Item Number:	Thread:	Pipe Body:	Eye Diameter:	Length:	Work Load Limit:
EESSTB3/16	3/16"	2-3/4"	5/16"	3-3/4"	320 lbs.
EESSTB1/4	1/4"	3-1/2"	3/8"	5"	450 lbs.
EESSTB5/16	5/16"	4-3/4"	9/16"	6-5/16"	850 lbs.
EESSTB3/8	3/8"	6"	5/8"	8"	1260 lbs.

Hook and Hook Turnbuckle s.s. T316



Item Number:	Thread:	Pipe Body:	Length:	Work Load Limit:
HHSSTB5/32	5/32"	2-5/16"	3-3/8"	180 lbs.
HHSSTB3/16	3/16"	2-3/4"	3-3/4"	320 lbs.
HHSSTB1/4	1/4"	3-1/2"	5"	450 lbs.
HHSSTB5/16	5/16"	4-3/4"	6-5/16"	850 lbs.
HHSSTB3/8	3/8"	6"	8"	1260 lbs.

Tensioning Systems

Jaw and Jaw Open Turnbuckle s.s. T316



Item Number:	Thread:	Pipe Body:	Pin Diameter:	Jaw Opening:	Length:
JJOTB316SS3/16	3/16"	2-3/4"	3/16"	1/4"	4-1/2"
JJOTB316SS1/4	1/4"	3-9/16"	1/4"	5/16"	5-3/8"
JJOTB316SS5/16	5/16"	4-5/8"	5/16"	3/8"	7-1/8"
JJOTB316SS3/8	3/8"	6"	5/8"	7/16"	8-3/4"

Open Turnbuckle Body s.s. T316



Item Number:	Thread:	Length:
SSTBBO5/32	5/32"	2-5/16"
SSTBBO3/16	3/16"	2-3/4"
SSTBBO1/4	1/4"	3-1/2"
SSTBBO5/16	5/16"	4-3/4"
SSTBBO3/8	3/8"	6"

Pipe Turnbuckle Body s.s. T316



Item Number:	Thread:	Length:
SSTBBP3/16	3/16"	3-5/16"
SSTBBP1/4	1/4"	3-3/4"
SSTBBP5/16	5/16"	4-3/16"
SSTBBP3/8	3/8"	5"

Tensioning Systems

Jaw and Jaw Pipe Turnbuckle s.s. T316



Item Number:	Thread:	Pipe Body:	Pin Diameter:	Jaw Opening:	Length:
JJPTB316SS3/16	3/16"	2-5/16"	3/16"	1/4"	5-3/16"
JJPTB316SS1/4	1/4"	3-3/4"	1/4"	5/16"	6"
JJPTB316SS5/16	5/16"	4-3/16"	5/16"	7/16"	7-5/16"
JJPTB316SS3/8	3/8"	5"	3/8"	1/2"	8-3/4"

Toggle and Toggle Pipe Turnbuckle s.s. T316



Item Number:	Thread:	Pipe Body:	Jaw Opening:	Length:
PTTSS316TB3/16	3/16"	2-5/16"	1/4"	5-1/4"
PTTSS316TB1/4	1/4"	3-3/4"	5/16"	5-3/4"
PTTSS316TB5/16	5/16"	4-3/16"	3/8"	7-5/16"
PTTSS316TB3/8	3/8"	5"	7/16"	8-1/2"

Drop Pin and Swage Stud Turnbuckle s.s. T316



* Hand Swage

Item Number:	Cable:	Thread:	Pipe Body:	Pin Rod Diameter:
DPSS316TB1/4-1/8-HS*	1/8"	1/4"-20	3-3/4"	0.25"
DPSS316TB1/4-3/16-HS*	3/16"	1/4"-20	3-3/4"	0.25"

Tensioning Systems

Stub End Turnbuckle - s.s. T316



Item Number:	Thread:	Pipe Body:	Length:	Work Load Limit:
SESE316SSTB3/16	3/16"	2-3/4"	8"	320 lbs.
SESE316SSTB1/4	1/4"	3-1/2"	10"	450 lbs.
SESE316SSTB5/16	5/16"	4-3/14"	12"	850 lbs.
SESE316SSTB3/8	3/8"	6"	16"	1260 lbs.

End Fittings

Swage Stud s.s. T316



Item Number:	Cable:	Thread:	Swage Body:	Length:
SS316SS1/4-20RH	1/8"	1/4"-20	2"	4"
EFTSS1/4X20-1/8-L	1/8"	1/4"-20 (Left Hand)	2"	4"
EFTSS1/4-3/16	3/16"	1/4"-20	2-1/2"	4-1/2"
EFTSS1/4X20-3/16-L	3/16"	1/4"-20 (Left Hand)	2-1/2"	4-1/2"
EFTSS5/16-1/4	1/4"	5/16"-18	3-1/8"	5-1/2"
EFTSS5/16X18-1/4-L	1/4"	5/16"-18 (Left Hand)	3-1/8"	5-1/2"
EFTSS3/8-1/4	1/4"	3/8"-16	3-3/16"	6"
EFTSS3/8X16-1/4-L	1/4"	3/8"-16 (Left Hand)	3-3/16"	6"

Hand Swage XL Swage Stud s.s. T316



* Hand Swage

Item Number:	Cable:	Thread:	Swage Body:	Length:
EFTSS1/4-1/8-XL-HS*	1/8"	1/4"-20	2"	7-1/2"
EFTSS1/4-3/16-XL-HS*	3/16"	1/4"-20	2-3/8"	8"

End Fittings

Hand Swage Stud s.s. T316



* Hand Swage

Item Number:	Cable:	Thread:	Length:
EFTSS1/4-1/8-HS*	1/8"	1/4"-20 x 1-7/8"	3-3/4"
EFTSS1/4-3/16-HS*	3/16"	1/4"-20 x 1-7/8"	3-3/4"

Hand Swage Short Stud s.s. T316



* Hand Swage

Item Number:	Cable:	Thread:	Length:
EFTSS1/4-1/8-HS-S*	1/8"	1/4"-20 x 3/8"	2-3/8"
EFTSS1/4-3/16-HS-S*	3/16"	1/4"-20 x 3/8"	2-3/8"

Lifeline Threaded Stud s.s. T316



* Hand Swage

Item Number:	Cable:	Thread:	Length:
EFLTSS1/4-1/8	1/8"	1/4"-20 x 2-1/2"	4-1/4"
EFLTSS1/4-3/16	3/16"	1/4"-20 x 2-1/2"	4-1/4"
EFLTSS1/4-1/8-HS*	1/8"	1/4"-20 x 2-1/2"	4-1/4"
EFLTSS1/4-3/16-HS*	3/16"	1/4"-20 x 2-1/2"	4-1/4"
EFLTSS5/16-1/4	1/4"	5/16"-18 x 2-1/2"	4-3/4"
EFLTSS3/8-1/4	1/4"	3/8"-16 x 3"	5-1/4"

End Fittings

Swage Toggle s.s. T316



Item Number:	Cable:	Pin Diameter:	Jaw Opening:	Length:
EFSTS1/8	1/8"	0.23"	0.38"	3"
EFSTS3/16	3/16"	0.23"	0.40"	4-1/8"
EFSTS1/4	1/4"	0.31"	0.50"	5"

Swage Marine Eye s.s. T316



Item Number:	Cable:	Eye Diameter:	Length:
EFMES1/8	1/8"	9/32"	2-9/16"
EFMES3/16	3/16"	3/8"	3-5/8"
EFMES1/4	1/4"	1/2"	4-1/8"

Swage Jaw s.s. T316



Item Number:	Cable:	Pin Diameter:	Jaw Opening:	Length:
EFSJS1/8	1/8"	3/16"	5/16"	2-5/8"
EFSJS3/16	3/16"	5/16"	1/2"	3-1/2"
EFSJS1/4	1/4"	7/16"	9/16"	4-1/8"

End Fittings

Fork Swage s.s. T316



Item Number:	Cable:	Pin Diameter:	Jaw Opening:
EFSWS1/8	1/8"	0.25"	0.32"
EFSWS3/16	3/16"	0.32"	0.40"
EFSWS1/4	1/4"	0.36"	0.47"

Deck Toggle Swage s.s. T316



Item Number:	Cable:	Eye Holes:	Eye Spacing:	Length:
EFSDTS1/8	1/8"	0.25"	1.30"	3"
EFSDTS3/16	3/16"	0.32"	1.30"	3-3/4"
EFSDTS1/4	1/4"	0.36"	1.56"	5"

Stemball Swage s.s. T316



Item Number:	Cable:	Length:
EFSSS1/8	1/8"	1.25"
EFSSS3/16	3/16"	1.38"
EFSSS1/4	1/4"	1.90"

End Fittings

Dome Swage s.s. T316



Item Number:	Cable:	Length:
EFDSS1/8	1/8"	2-1/4"
EFDSS3/16	3/16"	2-3/8"
EFDSS1/4	1/4"	2-13/16"

Hand Swage Lag Stud s.s. T316



* Hand Swage

Item Number:	Cable:	Eye Holes:	Eye Spacing:	Length:
EFLSS1/4-1/8-HS*	1/8"	0.25"	1.30"	3"
EFLSS1/4-3/16-HS*	3/16"	0.32"	1.30"	3-3/4"

Hand Swage Jaw s.s. T316



* Hand Swage

Item Number:	Cable:	Pin Diameter:	Jaw Opening:	Length:
EFSJS1/8-HS*	1/8"	0.20"	0.28"	2.15"
EFSJS3/16-HS*	3/16"	0.31"	0.38"	2.75"

End Fittings

Hand Swage Toggle s.s. T316



* Hand Swage

Item Number:	Cable:	Pin Diameter:	Jaw Opening:	Length:
EFSTS1/8-HS*	1/8"	0.20"	0.23"	2.50"
EFSTS3/16-HS*	3/16"	0.23"	0.40"	3.40"

Hand Swage Deck Toggle s.s. T316



* Hand Swage

Item Number:	Cable:	Eye Holes:	Eye Spacing:	Length:
EFSDTS1/8-HS*	1/8"	0.25"	1.30"	3"
EFSDTS3/16-HS*	3/16"	0.25"	1.30"	3-3/4"

Hand Swage Drop Pin Stud s.s. T316



* Hand Swage

Item Number:	Cable:	Pin Rod Diameter:	Length:
EFDPS1/4-1/8*	1/8"	0.25"	4"
EFDPS1/4-3/16*	3/16"	0.25"	4"

End Fittings

Stud Receiver s.s. T316



Item Number:	Threaded End:	Thread:	Head Diameter:	Length:
EFTR1/4-1/8-3/16	0.38"	1/4"	0.70"	2-3/16"
EFTR5/16-1/4	0.48"	5/16"	0.70"	2-3/16"

Invisi-Stud s.s. T316



Item Number:	Cable:	Thread:	Length:
EFTSS1/4X20-1/8-INV	1/8"	1/4"-20	2.70"
EFTSS1/4-3/16-INV	3/16"	1/4"-20	2.70"
EFTSS5/16-1/4-INV	1/4"	5/16"-8	2.70"

Adjustable Swage Stud s.s. T316



Item Number:	Cable:	Thread:	Threaded Space:	Length:
EFSSA1/4-1/8	1/8"	1/4"-20	1-1/2"	3-1/2"
EFSSA1/4-3/16	3/16"	1/4"-20	1-3/4"	4"
EFSSA5/16-1/4	1/4"	5/16"-18	2"	4-5/8"

End Fittings

Streamline Fixed Jaw s.s. T316



Item Number:	Cable:	Pin Diameter:	Jaw Opening:	Length:
EFSFJSS-1/8	1/8"	0.23"	0.25"	2.30"
EFSFJSS-3/16	3/16"	0.23"	0.25"	2.30"

Streamline Adjustable Jaw s.s. T316



Item Number:	Cable:	Pin Diameter:	Jaw Opening:	Swage End Length:
EFSAJSS-1/8	1/8"	0.23"	0.25"	3"
EFSAJSS-3/16	3/16"	0.23"	0.25"	3"

Flat End s.s. T316



Item Number:	Thread:	Outer Diameter:
SSFE1/4RH	1/4"-20	5/8"
SSFE1/4LH	1/4"-20 (Left Hand)	5/8"
SSFE5/16RH	5/16"-18	11/16"
SSFE5/16LH	5/16"-18 (Left Hand)	11/16"

Additional Hardware

Threaded Lag Insert s.s. T316



Item Number:	Threaded:	Outer Diameter:
SSTLI1/4	1/4"-20	1/2"
SSTLI1/4LH	1/4"-20	1/2"
SSTLI5/16	5/16"-18	1/2"

Plain Lag Insert s.s. T316



Item Number:	Inner Diameter:	Outer Diameter:
SSPLI9/32	9/32"	1/2"
SSPTLI3/8	3/8"	1/2"

Hanger Bolt s.s. T316



Item Number:	Thread:	Threaded Length:	Length:
SSHB1/4X20LH	1/4"-20 (Left Hand)	1-3/4"	3-3/4"
SSHB5/16X18LH	5/16"-18 (Left Hand)	2-1/4"	5"
SSHB3/8X16LH	3/8"-16 (Left Hand)	2-1/4"	5-1/2"

Additional Hardware

Dome Nut s.s. T316



Item Number:	Threaded:	Height:
--------------	-----------	---------

SSDN1/4RH	1/4"	1/2"
-----------	------	------

SSDN5/16RH	5/16"	9/16"
------------	-------	-------

SSDN3/8RH	3/8"	3/4"
-----------	------	------

Ball End s.s. T316



Item Number:	Threaded:	Diameter:
--------------	-----------	-----------

SSBE1/4RH	1/4"-20	1/2"
-----------	---------	------

SSBE1/4LH	1/4"-20 (Left Hand)	1/2"
-----------	---------------------	------

SSBE5/16LH	5/16"-18	11/16"
------------	----------	--------

SSBE5/16RH	5/16"-18 (Left Hand)	11/16"
------------	----------------------	--------

Hex Nut s.s. T316



Item Number:	Thread:	Thickness:
--------------	---------	------------

SSHN1/4RH	1/4"-20	0.22"
-----------	---------	-------

SSHN5/16RH	5/16"-18	0.26"
------------	----------	-------

SSHN3/8RH	3/8"-16	0.32"
-----------	---------	-------

SSHN1/4LH	1/4"-20 (Left Hand)	0.22"
-----------	---------------------	-------

SSHN5/16LH	5/16"-18 (Left Hand)	0.26"
------------	----------------------	-------

SSHN3/8LH	3/8"-16 (Left Hand)	0.32"
-----------	---------------------	-------

Additional Hardware

Threaded Rod s.s. T316



Item Number:	Threaded:	Length:
SSTH1/4X20	1/4"-20	4-1/3"
SSTH5/16X18	5/16"-18	4-3/4"
SSTH3/8X16	3/8"-16	5-1/4"

Flat Washer s.s. T316



Item Number:	Inner Diameter:	Outer Diameter:
SSW1/4	1/4"	1/2"
SSW5/16	5/16"	5/8"
SSW3/8	3/8"	7/8"

Non Welded Lag Eye Bolt s.s. T316



Item Number:	Thickness:	Eye Diameter:	Length:
SSLS1/4X4	1/4" LAG	0.50"	4"
SSLS5/16X3	5/16" LAG	0.64"	3"
SSLS3/8X3	3/8" LAG	0.64"	3"

Additional Hardware

Non Welded Eye Bolt s.s. T316



Item Number:	Thread:	Threaded Length:	Rod Length:	Eye Diameter:
NWEBSS1/4X4	1/4"	2-1/2"	4"	1/2"
NWEBSS1/4X5	1/4"	3"	5"	1/2"
NWEBSS1/4X6	1/4"	4"	6"	1/2"
NWEBSS5/16X3	5/16"	1-1/2"	3"	5/8"
NWEBSS5/16X4	5/16"	2-1/2"	4"	5/8"
NWEBSS3/8X4	3/8"	2-1/2"	4"	3/4"
NWEBSS3/8X5	3/8"	3"	5"	3/4"
NWEBSS3/8X6	3/8"	4"	6"	3/4"

30° Angled Washer s.s. T316



Item Number:	Size:	Inner Diameter:	Outer Diameter:
SSAW-1/4	1/4"	1/4"	5/8"
SSAW-5/16	5/16"	5/16"	11/16"
SSAW-3/8	3/8"	3/8"	11/16"

Standoff Washer for Round Post s.s. T316



Item Number:	Size:	Post:	Inner Diameter:	Outer Diameter
SSSW-516-RP	5/16"	2"	5/16"	5/8"
SSSW-716-RP	7/16"	2"	7/16"	11/16"

Additional Hardware

30° Countersunk Angle Washer s.s. T316



Item Number:	Size:	Inner Diameter:	Outer Diameter:
SSCAW-1/4	1/4"	1/4"	5/8"
SSCAW-5/16	5/16"	5/16"	11/16"
SSCAW-3/8	5/8"	5/8"	11/16"

30° Countersunk Angle Washer for Round Post s.s. T316



Item Number:	Size:	Post:	Inner Diameter:	Outer Diameter:
SSCAW-1/4-RP	1/4"	2"	1/4"	5/8"
SSCAW-5/16-RP	5/16"	2"	5/16"	11/16"
SSCAW-3/8-RP	3/8"	2"	3/16"	11/16"

Sleeve s.s. T316



Item Number:	Inner Spacing:	Width:	Height:	Length:
SS316SLEEVE1/8	1/8"	0.36"	0.25"	3/8"
SS316SLEEVE3/16	3/16"	0.55"	0.34"	1"
SS316SLEEVE1/4	1/4"	0.70"	0.43"	1-1/8"

Additional Hardware

Plain Ball Swage s.s. T316



Item Number:	Inner Diameter:	Outer Diameter:
SS316PBS1/8	1/8"	0.352"
SS316PBS3/16	3/16"	0.495"
SS316PBS1/4	1/4"	0.626"

Single Shank Ball Swage s.s. T316



Item Number:	Size:	Ball Diameter:
SS316SSBS1/8	1/8"	0.350"
SS316SSBS3/16	3/16"	0.492"
SS316SSBS1/4	1/4"	0.629"

Double Shank Ball Swage s.s. T316



Item Number:	Size:	Ball Diameter:
SS316DSBS1/8	1/8"	0.345"
SS316DSBS3/16	3/16"	0.487"
SS316DSBS1/4	1/4"	0.624"

Stainless Steel Cable

1x19 Cable s.s. T316



Item Number:	Diameter:	Work Load Limit:
LF-SS316-1X19-1/8	1/8"	420 lbs.
LF-SS316-1x19-3/16	3/16"	940 lbs.
LF-SS316-1X19-1/4	1/4"	1640 lbs.

Tools

Hand Swage Tool s.s. T316



Item Number:	Cable Size:
HST-1/8-3/16	1/8", 3/16"
HST-1/4	1/4"